



FLEX-ON™ SOFTWALL HOSE

FLEX-ING® brand FLEX-ON™ softwall hoses provide a highly flexible, economical alternative to hardwall hose. Softwall hoses offer additional flexibility making them ideal for reel or retractor applications where longer hose lengths are required.

HIGHLIGHTS

- Available in ¾" and 1" diameters, a variety of curb and whip hose lengths, and fixed or swivel fitting options.
- Available with swivel fitting option for enhanced ease of use.
- The minimally designed structure promotes the high flexibility perfect for longer length applications requiring a retractor or reel.
- The lightweight design is ideal for longer length applications to ensure easy maneuverability of the hose over long distances.
- An integrated fitting spring extends inside the ¾" hose to provide extra strength and prevent kinking at hose ends.

SPECIFICATIONS

- Tube: Nitrile synthetic rubber
- Cover: Synthetic rubber
- Fittings: Machined nickel-plated carbon steel with chrome finish
- Reinforcement: Spiral synthetic yarn with static wire
- Temperature rating: -40 °F to 140 °F (-40 °C to 60 °C)
- For use with gasoline, diesel, Ethanol blends (up to E10) and Biodiesel blends (up to B5).

Approvals/Certifications

- UL and cUL listed (UL 330, CAN/ULC-S612).

ORDERING INFORMATION

Ordering Guide

Complete part numbers have a specific order and are created using the following guidelines:

FLXSW A B C D

FLXSW = FLEX-ON™ Softwall Hose

A = Hose Diameter

2 = ¾"

3 = 1"

B = Hose Length Feet

Use three-digit format

C = Hose Length Inches

Use two-digit format

D = Swivel Options

Blank = No Swivels

SWOE = Swivel on one end

SWEE = Swivel on both ends

Example: FLXSW201006SWOE = FLEX-ON™ softwall hose, ¾" diameter, 10 feet, 6 inches, swivel on one end.